PRODUCT CARD NEX APP WITH SPIRAL AND STRAIGHT CABLE





Producer:

HeatQ Technology Sp. z o.o. 80-017 Gdańsk Trakt Św. Wojciecha 223/225 Tel.: +48 585 805 104/+48 691 209 888 www.heatq.com e-mail: biuro@heatq.com





INTENDED USE

Electric heating element with controller, radio communication 868 MHz and Bluetooth module. Radiator equipped with the electric heating element with NEX thermostat performs function of electric dryer, space heater or hybrid combining to the electric dryer and standard radiator connected to the central heating. Due to intuitive operation the device programming is simply and user-friendly, including the operation of mobile application NEX APP available on App Store and Google Play.

3. Power cable

TYPES OF CONNECTION

- spiral cable
- straight cable


COLOURS OF THERMOSTATS:

chrome, white, black, black mat, silver


TECHNICAL PARAMETERS

- nominal voltage: option 1:230V, 50Hz; option 2: 110V, 60 Hz
- insulation class: option 1: Class I; option 2: Class II
- ingress protection class: IPX5 (ZONE 2 i 3)
- power: 120W, 200W, 300W, 400W, 500W, 600W, 800W, 1000W, 1200W

DIMENSION AND WEIGHT						
Power	Weight	Lenght "l"	Lenght "L"			
120W	0,40kg	310 mm	377mm			
200W	0,39kg	270mm	327mm			




Source: NORM PN-EN 60529:2003



300W	0,40kg	295mm	362mm
40014	0.441	220	207
400W	0,41kg	330mm	397mm
F00)4/	0.424	245	412.00.00
500W	0,42kg	345mm	412mm
600) <i>1</i> /	0.401	200	407
600W	0,42kg	360mm	427mm
800W	0,45kg	470mm	537mm
80077	0,45Kg	47011111	55711111
1000W	0,48kg	560mm	627mm
100011	0,1018	3001111	027.1111
1200W	0,49kg	565 mm	637mm
120000	0,49Kg		03711111

		ŗ		3
1.	Heating element		ezum	2
2.	Controller housing		67	
3	Power cable	1		

H = AECHNOLOGY





FUNCTIONALITY OF THE NEX APP

- remote control via the application on a mobile device controller rotation in the range of 0° 330°
- daily and weekly work schedule
- energy consumption meter
- measuring the room temperature/ stopping the heating function for the time the window/door is open.
- timers: TURBO, START-STOP, DELAYED START
- 4-stage temperature regulation in the range of 30°-60°C

- **ANTIFREEZE** function
- two-level overheating protection
- additional protection against working when "dry"
- low power consumption in standby mode (Ultra-Low-Power)
- dryer function
- intelligent work control microprocessor control
- visualization in colorful LED technology
- free application NEX APP on App Store and Google Play

INDEX						
Product	Type of connection	Colours	Power	Package	Optional equipment	
PNX2 – ELECTRIC HEATING ELEMENTS NEX APP	PC – straight cable with the plug	WX - white	22 - 120W	B – carton without the print	T- tee	
	PX – straight cable without the plug	BX - black	02 - 200W	O – carton with the print	ST – additional temperatue sensor	
	SC – spiral cable	BO – black mat	03 - 300W	R - foil	OW – open window/door sensor	
		SX - silver	04 - 400W		 - free application to download on Google Play and App Store 	
		CX - chrome	06 - 600W			
			08 - 800W			
			10 - 1000W			
			0C - 1200W			

Example of index: PNX2SCCX03B

PNX2 – ELECTRIC HEATING ELEMENT NEX APP

- SC MASKING CABLE
- CX COLOR OF THERMOSTAT CHROME
- **03** POWER 300 W
- **B** CARTON WITHOUT THE PRINT

Producer: HeatQ Technology Sp. z o.o. 80-017 Gdańsk, Trakt Św. Wojciecha 223/225 Tel.: +48 585 805 104/+48 691 209 888 Date: 29.10.2020 r. www.heatq.com e-mail: biuro@heatq.com Prepared by: Urszula Wasielewska

HEATO TECHNOLOGY